

## METAL DETECTOR APPLICATION SHEET

## **METAL DETECTOR**



## **CONTACT INFORMATION**

NAME
COMPANY NAME
CITY
STATE
PHONE
F-MAIL

## **APPLICATION DATA**

BELT WIDTH:
BELT SPEED:
MATERIAL CONVEYED:
BELT BURDEN DEPTH "A":
A
IDLER CENTER DISTANCE:
IS THERE A SPLICE ON THE BELT:  □ YES □ NO
IS A MARKING SYSTEM REQUIRED: ☐ YES ☐ NO
TYPE OF MARKING SYSTEM:  □ PAINT □ BEAN BAG □ OTHER
DISTANCE FROM DETECTOR TO AMPLIFIER:(30 FT STANDARD)
POWER REQUIREMETS (110 VAC/60Hz STD): □ 110 VAC □ 220 VAC □ 50 Hz □ 60 Hz
SMALLEST PIECE OF METAL TO BE DETECTED:
(EI:SIZE OF MACHINERY NUT 1/2", 5/8",3/4",1") □ 1/2" □ 5/8" □ 3/4" □ 1"
ADDITIONAL INFORMATION:
All dimensions and specifications subject to change without notice.

Certified dimensions and specifications of ordered material available on request. Copyright © 2020, Douglas Manufacturing Co., Inc. All rights reserved.